

# GXR-SERIES

High Frequency X-ray Generator

## Excellent Performance and Stability!

### Features

- Full Auto mA calibration, kV calibration, kV & mA feedback waveform display and analysis
- Adaptive mA calibration automatically compensates filament aging
- Easy parameter setting and Firmware upgrade
- System diagnosis, Error log and Statistical data display
- Remote Diagnosis via Internet reduces service cost and down time
- Realtime monitoring self diagnosis and Error code display
- Tube anode HU display & protection, tube overload & housing overheat protection
- Anatomical programs with APR utility: support user programmable 1,280 conditions
- Dual speed starter: Direct drive by 6-pack IPM circuit, No need for shift capacitor, Dynamic brake



### Option

- AEC (Automatic Exposure Control) Interface
- DR (Digital Radiography) Interface: SDK, PC interface module, Signal interface
- Pedestal Console Stand



## Specification

Model	GXR-32	GXR-40	GXR-52	GXR-68	GXR-82
Output Rating	32kW	40kW	52kW	68kW	82kW
Line Nominal, Phase	230VAC, 1Φ 400/480VAC, 3Φ		400/480VAC, 3Φ		
Line Voltage Range	±10% (Frequency: 50*/60Hz), * : Outside North America				
kV Range	40~125kV, 1kV step Optional 40~150kV		40~150kV, 1kV step		
mA Range	10 to 400mA Optional 500mA	10 to 500mA	10 to 640mA	10 to 800mA	10 to 1,000mA
Timer Range	0.001 to 10 sec, 38 steps				
mAs Range	0.1 to 500mAs (Optional higher mAs)				
Max. Power Output	400mA@80kV 320mA@100kV 250mA@125kV 125mA@150kV(1Φ) 200mA@150kV(3Φ)	500mA@80kV 400mA@100kV 320mA@125kV 160mA@150kV(1Φ) 250mA@150kV(3Φ)	640mA@81kV 500mA@104kV 400mA@130kV 320mA@150kV	800mA@85kV 640mA@106kV 500mA@136kV 400mA@150kV	1,000mA@82kV 800mA@102kV 640mA@128kV 500mA@150kV
Rotor Supply	Low Speed Dual Speed (Option for 3Φ)		Dual Speed (Option for GXR-52)		
Reproducibility	Coefficient of Variation: kV<0.005, Time<0.005, mAs<0.01				
Accuracy	kV < ±(1%+1kV), mA < ±(3%+1mA), Time < ±(1%+0.5ms), mAs < ±(3%+0.1mAs)				
Linearity	Coefficient of Linearity < 0.01 : CL = (X1-X2)/(X1+X2), where X is mR/mAs				
Anatomical Programs	User Programmable max. 1,280 programs with APR utility software				
Technique Selection	4 point display (kV, mA, Time, mAs)				
Image Receptors	2 Bucky + 1 Non-Bucky				
Auxiliary Power Supply	External System Power		230VAC, 1A, 230W		
	Magnetic Lock Power		110VAC, 1A, 110W		
	Magnetic Lock Power		28VDC, 5A, 140W		
	Collimator Lamp Power		24VAC, 6.3A, 150W		

## Dimension

